

3D PLUS SPACE CAMERA SYSTEMS P/N DECODER

	1	2	3	4	5	6	7	8	9		
	3DCS	00M	00	0000	-	0	X	X	X	0000	X
Example =>	3DCS	04M	08	1234	-	1	B	B	A	5678	W

Ex: 3DCS04M081234-1 BB A5678W

1 Sensor Resolution

00M: Sensor resolution in megapixels

2 Objective Focal Length

00: Objective focal length in mm

3 Control Features

nnnn: Product Flyer / Datasheet number

4 System Revision

0: Revision Number

5 Temperature range

B: -40 °C to +55°C

F: -55 °C to +55°C

S: Specific

6 Screening level

B: Industrial grade

S: Space grade

7 Camera Testing Options

/ : Default Acceptance Tests

A: Extended Acceptance Tests

S: Specific

8 Configuration Features

nnnn: Critical Item Data List (CIDL) number, defining details of camera module including flex cable and FPGA design, optical assembly, and mechanical design

9 External Coating options

Only Applicable to Mechanical Casing and objective barrel

: No option by default

W: White Paint External Coating

B: Black Paint External Coating

S: Specific

3D PLUS S.A.S. reserves the right to change without notice – 3DPI-1124-2 -Revision 25/03/2024.